

## Tubo Pro Surface

83W / 7990lm / 4000K / DALI / Wide flood  
76° / 2984mm

64916



Design: Eduardo Souto de Moura  
Surface luminaire with tubular semi frosted PMMA body with 70mm diameter.  
Clear polycarbonate end caps with marked installation angles.  
Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.  
Equipped with 2m cable (5x0.75 mm²).  
Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
Power supply included.  
IP44 | 230Vac | 50/60Hz



| LED        | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 83W          | 95,4W     |
| Flux       |       | 11750lm      | 7990lm    |
| Efficiency |       | 142lm/W      | 84lm/W    |
| LOR        |       | -            | 68%       |
| UGR        |       | -            | <19       |



Beam angle  
Wide flood 76°

Application



Weight



Finishes

○ .01 White / RAL 9010

Mandatory

43707 Surface fitting accessory

Data according to regulations  
2019/2020/EU supplemented by 2021/341 [2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class E  
Model Identifier 4053560084