


26W / 1250lm / 4000K / DALI / Spot 17° /  
1211mm

65398



Design: O/M + Bartenbach GmbH  
Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.


Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision35 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source.

Fitting accessories for pendant version ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



	<b>4000K</b>	<b>Light Source</b>	<b>Luminaire</b>
<b>Power</b>	<b>26W</b>	<b>30,7W</b>	
<b>Flux</b>	<b>2845lm</b>	<b>1250lm</b>	
<b>Efficiency</b>	<b>113lm/W</b>	<b>41lm/W</b>	
<b>LOR</b>	-	<b>44%</b>	
<b>UGR</b>	-	<b>&lt;10</b>	



Application



Weight  
2,4Kg

mm

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

54036 Pendant direct fitting accessory  
56051 Clear Base DALI  
ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

