

Beam



Beam

Clean, modern, and attractive, Beam is the classic downlight for every need in general and detail lighting. Its latest evolution is made completely in die-cast alloy for a distinctive finish, and features a more affordable design, construction, and even simpler and easier installation.



Beam

Body

Aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish. Stainless steel springs.

Diffuser

Diffused beam version supplied with prismatic acrylic diffuser IP54. Acrylic clear diffuser for non-diffuse beam versions supplied separately to increase the protection level up to IP54.

Accessories

Fitting accessories for different applications are available.

Light source

O/M LED modules with excellent colour consistency (2 step-MacAdam) and long operating lifespan (>50.000h; L80/B10). LED CRI>90 2700K; CRI>80 3000K, 4000K.



Adjustable

The luminaire can be oriented by the horizontal and vertical axes.



Suitable for wet areas, IP54.




Beam

Trim/Trimless
Ø75mm

Beam

Trim/Trimless
Ø100mm




Spot




Medium



Flood



Diffuse



Wallwasher



Accessories

Recessing accessory, available separately, for trimless version.

Finishes

○ .01 White

● .02 Black

Beam



Not included

Recessing accessory for trimless version

59021 

59022 


Beam IP54 clear diffuser $\phi 39 \times 3 \text{mm}$

59023


Beam IP54 clear diffuser $\phi 60,5 \times 3 \text{mm}$

59024



Beam



Spot



Medium



Flood




Ceiling-recessed luminaire made of aluminium die-cast. IP54 version available. Accessory for flush installation in false ceilings supplied separately.


LED CRI>90 2700K; CRI>80 3000K, 4000K / >50.000h, L80/B10
2-step MacAdam / power supply included



IP20/IP54 | 230Vac | 50/60Hz



Wallwasher



	Luminaire Dimensions	Light Source Power	Light Source Flux	Luminaire Flux	On/Of Code	DALI Code
Beam						
	ø75					
2700K						
Spot 14°	ø75x105	2,2W	200lm	180lm	60326	60331
Medium 23°	ø75x105	7,4W	720lm	530lm	60327	60332
	ø75x105	10W	955lm	700lm	60328	60333
Flood 35°	ø75x105	7,4W	720lm	550lm	60329	60334
	ø75x105	10W	955lm	730lm	60330	60335
3000K						
Spot 14°	ø75x105	2,2W	215lm	190lm	60336	60341
Medium 23°	ø75x105	7,4W	895lm	660lm	60337	60342
	ø75x105	10W	1190lm	880lm	60338	60343
Flood 35°	ø75x105	7,4W	895lm	680lm	60339	60344
	ø75x105	10W	1190lm	900lm	60340	60345
4000K						
Spot 14°	ø75x105	2,2W	305lm	270lm	60346	60351
Medium 23°	ø75x105	7,4W	935lm	690lm	60347	60352
	ø75x105	10W	1240lm	910lm	60348	60353
Flood 35°	ø75x105	7,4W	935lm	710lm	60349	60354
	ø75x105	10W	1240lm	940lm	60350	60355

Finishes ○ .01 White ● .02 Black

	Luminaire Dimensions	Light Source Power	Light Source Flux	Luminaire Flux	On/Of Code	DALI Code
Beam						
	ø100					
2700K						
Medium 28°	ø100x118	10W	1100lm	820lm	60356	60362
	ø100x158	19W	2060lm	1540lm	60357	60363
Flood 45°	ø100x118	10W	1100lm	870lm	60358	60364
	ø100x158	19W	2060lm	1630lm	60359	60365
Wallwasher	ø100x118	10W	1100lm	890lm	60360	60366
	ø100x158	19W	2060lm	1670lm	60361	60367
3000K						
Medium 28°	ø100x118	10W	1400lm	1050lm	60368	60374
	ø100x158	19W	2650lm	1990lm	60369	60375
Flood 45°	ø100x118	10W	1400lm	1110lm	60370	60376
	ø100x158	19W	2650lm	2090lm	60371	60377
Wallwasher	ø100x118	10W	1400lm	1130lm	60372	60378
	ø100x158	19W	2650lm	2150lm	60373	60379
4000K						
Medium 28°	ø100x118	10W	1450lm	1090lm	60380	60386
	ø100x158	19W	2740lm	2050lm	60381	60387
Flood 45°	ø100x118	10W	1450lm	1150lm	60382	60388
	ø100x158	19W	2740lm	2160lm	60383	60389
Wallwasher	ø100x118	10W	1450lm	1180lm	60384	60390
	ø100x158	19W	2740lm	2220lm	60385	60391

Finishes ○ .01 White ● .02 Black

	Luminaire Dimensions	Light Source Power	Light Source Flux	Luminaire Flux	On/Of Code	DALI Code
Beam IP54						
	ø75					
2700K						
Spot 14°	ø75x100	2,2W	200lm	165lm	60392	60399
Medium 23°	ø75x100	7,4W	720lm	490lm	60393	60400
	ø75x100	10W	955lm	650lm	60394	60401
Flood 35°	ø75x100	7,4W	720lm	510lm	60395	60402
	ø75x100	10W	955lm	675lm	60396	60403
Diffuse	ø75x100	7,4W	720lm	390lm	60397	60404
	ø75x100	10W	955lm	520lm	60398	60405
3000K						
Spot 14°	ø75x100	2,2W	215lm	175lm	60406	60413
Medium 23°	ø75x100	7,4W	895lm	610lm	60407	60414
	ø75x100	10W	1190lm	815lm	60408	60415
Flood 35°	ø75x100	7,4W	895lm	630lm	60409	60416
	ø75x100	10W	1190lm	830lm	60410	60417
Diffuse	ø75x100	7,4W	895lm	490lm	60411	60418
	ø75x100	10W	1190lm	650lm	60412	60419
4000K						
Spot 14°	ø75x100	2,2W	305lm	250lm	60420	60427
Medium 23°	ø75x100	7,4W	935lm	640lm	60421	60428
	ø75x100	10W	1240lm	840lm	60422	60429
Flood 35°	ø75x100	7,4W	935lm	655lm	60423	60430
	ø75x100	10W	1240lm	870lm	60424	60431
Diffuse	ø75x100	7,4W	935lm	510lm	60425	60432
	ø75x100	10W	1240lm	670lm	60426	60433

	Luminaire Dimensions	Light Source Power	Light Source Flux	Luminaire Flux	On/Of Code	DALI Code
Beam IP54						
	ø100					
2700K						
Medium 23°	ø100x118	10W	1100lm	760lm	60434	60440
	ø100x158	19W	2060lm	1425lm	60435	60441
Flood 35°	ø100x118	10W	1100lm	805lm	60436	60442
	ø100x158	19W	2060lm	1510lm	60437	60443
Diffuse	ø100x118	10W	1100lm	650lm	60438	60444
	ø100x158	19W	2060lm	1210lm	60439	60445
3000K						
Medium 23°	ø100x118	10W	1400lm	970lm	60446	60452
	ø100x158	19W	2650lm	1840lm	60447	60453
Flood 35°	ø100x118	10W	1400lm	1030lm	60448	60454
	ø100x158	19W	2650lm	1935lm	60449	60455
Diffuse	ø100x118	10W	1400lm	830lm	60450	60456
	ø100x158	19W	2650lm	1560lm	60451	60457
4000K						
Medium 23°	ø100x118	10W	1450lm	1010lm	60458	60464
	ø100x158	19W	2740lm	1900lm	60459	60465
Flood 35°	ø100x118	10W	1450lm	1065lm	60460	60466
	ø100x158	19W	2740lm	2000lm	60461	60467
Diffuse	ø100x118	10W	1450lm	860lm	60462	60468
	ø100x158	19W	2740lm	1620lm	60463	60469

www.om-light.com

20.08.2020