

Structure

- ① Profile
- ② End caps
- ③ Fitting accessories
- ④ Profile coupling

Diffuser

- Ⓐ Polycarbonate frost diffuser

Light Source

- Ⓑ LED Modules

With light projecting both directly and indirectly, H45 is the go to when you want versatile diffusion and a profile that combines sleek, sophisticated lines with the timeless design.


Made-to-measure:

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks.

IP20 | 230Vac | 50/60Hz



Structure



Pendant

1 Profile

Aluminium profile. Unit=1m, maximum length per segment is 3m.

2 End caps

Set of two

3 Fitting accessories

Pendant fitting accessories

One 2m steel cable (Ø1,5mm) with millimetric height adjustment system.

One on each end of the profile segment and every 3m.

4 Profile couplings

One between two profile sections



Profile coupling linear



Profile coupling corner



Clear base
Clear base DALI
Clear base E-KIT



Aluminium base
Aluminium base DALI



Aluminium base E-KIT
Aluminium base DALI + E-KIT

Diffuser

A Polycarbonate frost diffuser

For all applications, friendly clipping system and double fitting system. Unit=1m, maximum length per segment is 3m.

Diffuser Total Size

Sum of all LED light sources + 20mm

Light source

B LED Modules

High-efficiency LED modules with excellent colour consistency and long operation lifespan. Drivers included.



General lighting

LED CRI>80 / >50.000h, L80/B10
3-step MacAdam

Total size of the H45 Made-to-measure

Profile length
Sum of all LED light sources* + 20mm

+



Set of Standard End caps +11mm

or



Set of Slim End caps +5mm

*Diffuse module length = Sum of all LED light sources + 20mm (+3mm between LED light sources)

Please add the finish code to the end of the profile and end caps code:

○ .01 White ● .02 Black ● .10 Anodised aluminium